

PRIMELUB

LICOM EP 2

PRODUCT DESCRIPTION

- ◆ PRIMELUB LICOM EP 2 are high quality special multipurpose lithium complex grease, with very high dropping point, anti rust, good resistance to water wash-out and high stability oxidation
- ◆ PRIMELUB LICOM EP 2 contain extreme-pressure and other proven additives to enhance their performance in a wide range of applications

APPLICATIONS

- ◆ Designed for multipurpose grease lubrication
- ◆ Heavy duty bearings and general industrial lubrication
- ◆ Heavy duty plain and rolling element bearings

AVAILABLE

- ◆ Primelub licom EP 2 are available in packing's 180 and 18 kg.

TECHNICAL SPECIFICATION

Test	Unit	Method	Spesification	Result
NLGI Grade			2	2
Colour		Visual	Red	Red
Appearance		Visual	Smooth, Tacky	Smooth, Tacky
Dropping Point Oil Bath	°C	ASTM D 566 ASTM D 2265	Min 265	278
Penetration@ 25 C Worked	Mm	ASTM D 217	265 - 295	276
Oil Separation, 30 hours 100°C	% wt	ASTM D 6184	Max 1.5	0.77
Copper Stripe Corrossion, 24 hours 100°C		ASTM D 4048	Max 2A	1A
Four Ball Wear, Scar Diameter	mm	ASTM D 2266	Max 0,60	0,562
Four Ball EP, Weld Point	kgf	ASTM D 2596	Min 250	315
Water Washout, 1hour 79 °C	% wt	ASTM D 1264	Max 1,5	0.92
Soap Type			Lithium Complex	Lithium Complex