

PRIGO HD

HEAVY DUTY



❖ DESCRIPTION PRODUCT

- high-performance gear Lubricant formulated from multi-functional additive for automotive and industry meet the requirements of the GL-4 and GL-5

❖ REKOMENDATION

- PRIGO HD meet the requirements API GL-5, MAN 342 M1, MAN 342 M2,ZF 05A, ZF 07A, ZF 08, ZF 12E, ZF 16B-D ZF 17B, ZF 21A, SCANIA STO 1:0, VOLVO 1273.10 SAE J2360, INDUSTRIAL, APIL GL-4 dan API MT-1.

❖ APPLICATION PRODUCT

- PRIGO HD used to lubricate manual transmissions and axles on vehicles and heavy equipment industries.

❖ CHARACTERISTICS PRODUCT

SAE	90	140	90 GL 5	140 GL 5
Specific density, 15°C	0.9015	0.9145	0.9025	0.9165
Viscosity Kinematic, at 40°C, cSt	150	343	148	345
100°C, cSt	15.1	26.1	14.9	26.4
Viscosity Index	101	100	100	101
Color ASTM	L 2.5	L.2.5	L 2.5	L 2.5
Flash Point. (COC). °C ASTM	200	200	200	200
Pour Point. °C	-18	-9	-18	-9