

PRENO SE SPECIAL ENGINE



❖ DESCRIPTION PRODUCT

- PRENO SE series is meet the requirements of Monograde lubricant API CF 2.
- With the formulation of a balanced additive and high-grade, antioksidant, antirust, anti foam.

❖ REKOMENDATION

- PRENO SE is meet the requirements API Services Classification CF-2/SG, MB 228.1, CCMC D4/G4PD2, MAN 271, VW 501.01/505.00, MIL-L-2104E, MIL-L46142D, MACK EO-K/2, VOLVO VDS,
- PRENO SE HD 10W is meet the requirements API Services Classification Allison C-4 dan Caterpillar TO-2

❖ APPLICATION PRODUCT

- PRENO SE series recommended for heavy duty diesel engine equipped with supercharger engine, transport and shipping.
- For the use of diesel engine injection with different types of fuels including with high sulphur content

❖ CHARACTERICS PRODUCT

SAE	HD 10W	30	40	50
Specific density, 15°C	0.8805	0.8895	0.8965	0.8975
Viscosity Kinematic, at 40°C, cSt	44	94	142	180
100°C, cSt	7	11	14.5	17
Viscosity Index	118	103	101	100
Flash Point. (COC). °C ASTM	224	243	250	252
Pour Point. °C	-33	-18	-15	-9
Total Base Number, mg KOH/g	10,3	10.5	10,5	10,5