

PRYDO AW

HIDRAULIC OIL

❖ DESKRIPSI PRODUK

- PRYDO AW hydraulic lubricants are formulated from mineral base oil and additive of high quality.
- Equipped additive anti wear, anti foam, anti oksidant.

❖ REKOMENDASI

- PRYDO AW hydraulic equipment to meet industries such as Denison HF-0, Vickers I-286s, M-2950-S and Cincinnati Milacron P-68 (PRYDO AW 32), P69 (FOR PRYDO AW 68) and P7- (FOR PRYDOW AW 46). and already meet the API SERVICES Parker (formerly denison) HF-0, HF-1, HF-2(HM,HV), Eaton m-2950-s and i-286-s3, MAG P68, P69, P70 (HM,HV), DIN 51224-(HM); DIN 51224-3(HV), ISO 11158 (HM,HV) ASTM D6158 (HM,HV), SAE MS 1004 (HM,HV), BOSCH REXROTH RE 90220, JCMAS PO41 HK HYDRAULIC SPECIFICATION, ANSI/AGMA 9005-E02-RO, GM LS-2 AIST 126, 127, SEB 181222.

❖ APLIKASI

- the whole hydraulic system of heavy equipment in mine industrial, industrial vehicles and estates
- Designed for the needs of the hydraulic system of the pump high-tech.

❖ SPESIFIKASI PRODUK

ISO Viscosity Grade	32	46	68	100
Specific density, 15°C	0.8735	0.8785	0.885	0.8905
Viscosity Kinematic, at 40°C, cSt	32	46	68	100
100°C, cSt	5.4	6.8	8.8	11.04
Viscosity Index	102	102	102	100
Color ASTM	1.0	1.5	2.0	2.5
Flash Point. (COC). °C ASTM	220	230	240	245
Pour Point. °C	-30	-28	-24	-24