

PRMELUB SWO

SLIDE WAY OIL

❖ DESCRIPTION OF PRODUCT

- PRIMELUB SWO is paraffin-based oil with a High Viscosity Index options, enriched with additive anti-oxidant, anti foam and oiliness additive-combined with special additives to make it tacky and sticky oil so that it can afford to not splatter/spray and protect ways.

❖ APPLICATION OF PRODUCT

- Recommended for lubrication of slides, ways, and carriages of all types of equipment such as grinding machines, pengetam, milling machines, shapers, horizontal honing machines, etc.

❖ BENEFIT OF PRODUCT

- The adhesion is very good, prevents the flow and splashing of oil when the engine is spinning fast or due to the vibrations of engine parts, minimizing dirt and contaminants in the material being processed.

❖ CHARACTERISTICS OF PRODUCT

| Typical Characteristic | Unit | Test Method | ISO VG 32 | | ISO VG 68 | |
|------------------------------|------|-------------|-----------|------|-----------|------|
| | | | Min | Max | Min | Max |
| Viscosity Kinematic, at 40°C | cSt | ASTM D 445 | 31.0 | 33.0 | 67.0 | 69.0 |
| Viscosity Index | - | ASTM 2270 | 110 | 118 | 105 | 115 |
| Color ASTM | | | | 1.0 | | 1.0 |
| Flash Point. (COC). | °C | ASTM D 92 | 200 | - | 200 | - |